

## K OIL

## Safety Data Sheet

Issue Date: January 2010

Page 1 of 2

Substance/Company Identification Product Name: Product Type:

Apiezon K Oil. Vacuum sealing oil.

CAS No:

8012-95-1, 64741-56-6.

Company Name:

M&I Materials Ltd.

Telephone: +44 (0)161 864 5409

Hibernia Way, Trafford Park, Manchester, M32 0ZD, UK. Fax: +44 (0)161 864 5444.

**Emergency Telephone:** 

+44 (0)161 864 5439.

Email:

RussellMartin@mimaterials.com.

2. Hazards Identification

4. First Aid Measures

This product is not classified as hazardous.

3. Composition/Ingredients

Composition:

Hydrocarbon oil.

None.

Hazardous Ingredients:

Irrigate with copious quantities of water.

Eyes: Skin:

Wash with soap and water.

Inhalation:

None envisaged.

Ingestion:

Do not induce vomiting. Obtain medical attention.

5. Fire Fighting Measures

Suitable extinguishing media:

Carbon dioxide, dry powder, foam

or water fog. Do not use water jets.

Special exposure hazards:

None.

Special protective equipment:

None.

6. Accidental Release Measures

Personal precautions:

Spilt product constitutes a slip hazard. Avoid contact

with eyes.

Environmental precautions:

Prevent entry into drains, sewers and

watercourses.

Cleaning procedures:

Soak up with absorbent granules. See para.

13 re disposal.

7. Handling and Storage

Handling: Storage:

No special precautions required. No special precautions required.

8. Exposure Controls/ **Personal Protection**  Substance

8hr TWA

<u>STEL</u>

Source

Mineral oil (mist)

5mg/m<sup>3</sup>

10mg/m<sup>3</sup>

EH40

Respiratory protection:

None required.

Hand protection:

Wash hands after use. For prolonged or repeated

skin contact gloves are recommended.

Eye protection:

None required.



## **KOIL**

Safety Data Sheet Continued

Page 2 of 2

9. Physical & Chemical Properties

Physical state: High viscosity liquid. Boiling point @ 1 Torr: 300°C. Colour: Brown black. Flash point (open): >350°C. >370°C. Odour: Fire point: Pungent. Water solubility: Insoluble. Autoignition point: Not determined. Relative density @ 20°C: 0.94. Explosive limits: Not determined.

10. Stability & Reactivity

Stability: Will not polymerise.

Conditions to avoid: Temperatures >200°C.

Materials to avoid: Strong oxidising agents.

Hazardous decomposition products: Trace amounts of polycyclic hydrocarbons and nitrogen dioxide.

11. Toxicological Information

Oral LD50 (rat) >2 g/kg.

Eyes:

May cause transient irritation.

Inhalation:

Low volatility makes inhalation unlikely.

Ingestion:

May cause nausea, vomiting and diarrhoea.

Skin:

Repeated and prolonged skin contact may cause skin disorders.

12. Ecological Information

Ecotoxicity: When used and/or disposed of as indicated no adverse

environmental effects are foreseen.

Mobility: Low volatility/ Low solubility in water. Persistence and degradability: Base oil slowly biodegradable in

aerobic conditions.

13. Disposal Considerations

Product and packaging must be disposed of in accordance with local and national regulations. May be incinerated. Unused product may be returned for reclamation.

14. Transport Classification

Not classified as hazardous under air (ICAO/IATA), sea (IMDG), road (ADR) or rail (RID) regulations.

15. Regulatory Information

Not classified as dangerous under EC criteria. All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

16. Other Information

Compiled according to the EU Directive 1907/2006/EC.

Changes from last issue: Section 1 Emergency telephone number.

The information provided in this Safety Data Sheet is correct to our best knowledge, information and belief at the date of its publication. It is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not be construed as guaranteeing any specific property of the product.